

# Timestrip®

Elapsed Time indicator

## TS201 1 Month Data Sheet

The Timestrip® 1 month indicator shows you when one month has passed so you can see when to replace a filter, dispose of an expired product or maintain equipment without having to write down and calculate dates. Timestrip indicators are single use, so remember to dispose of the old one after one month and activate a fresh one to start the cycle again. It is self-adhesive and splash proof, and expires 3 years after the manufacturing date shown on the bag. Timestrip indicators should be used in a room temperature environment or stuck to a room temperature surface (average 22 °C/72 °F). They are not suitable for outside use.

### Instructions for Use



1. Inactive



2. Active



3. Monitoring

1. Activation: Fully squeeze the activation button between thumb and finger. A red line will appear within 1-2 minutes to show that the Timestrip® has been activated. In the unlikely event that Timestrip® shows red before you activate it, there is no need to contact customer service. Simply discard and take a new one. 1 or 2 products per 100 count are always provided free of charge.
2. Peel off the backing liner and stick the Timestrip® to the product, material or device to be monitored\*.
3. Once activated, the red dye will indicate elapsed time by moving through the white window and past each time marker. The progress of the red dye is irreversible and each Timestrip® can only be used once.

### Specification

Type	Irreversible, single use
Temperature Sensitivity*	+22 °C/+72 °F Use in a room temperature environment, stick to a room temperature surface
Time window	1 Month. 1, 2, 3 weeks & 1 month markers
Activation Feature	A manual activation button on the top – a thin red line will appear and confirm it is activated.
Indication	Irreversible
Accuracy of Time	+/- 15% in isothermal conditions
Shelf Life	3 years.
Adhesive	Pressure sensitive, finger lift
Size	40mm x 19mm

Quality Assurance	Produced under ISO9001:2008
Recommended Storage	Room temperature: 22 °C/72 °F at 20-80% humidity. Cool dark environment
Packaging	Supplied loose in polybags of 100 units
Shipping Package Requirements	No special requirements as inert until activated
Protection	Splash proof
Product Construction	The indicator is constructed of a polymeric assembly multilayer and aluminium-plastic laminate. It encapsulates coloured oils. All materials are non-toxic, latex and PVC free.